

5. ACKNOWLEDGMENTS

The authors recognize John McCorkle of Freescale, Inc. for his leadership, insight, and insistence on the highest quality. We learned a great deal from working with John in all relevant technical areas.

This investigation required the services of a number of ITS engineers with a broad range of expertise, some of whom are not included in the list of authors. The authors recognize Brent Bedford for his expertise in test and measurement equipment and techniques; Randy Hoffman, Richard Statz, and Steve Engelking for developing much of the low level software routines needed to automate the experiment via software control; Stephen Wolf for his expertise in video quality assessment; Frank Sanders for sharing knowledge learned in previous interference tests on C-band earth station receivers [9]; Dr. Roger Dalke for his knowledge of random processes and experimental uncertainty analyses; Andrew Rogers and Michael Mitchell for their attention to detail in hardware production and signal characterization measurements; and Dr. William Kissick for his support and leadership.

6. REFERENCES

- [1] “First Report and Order in the matter of ET Docket 98-153 (Revision of Part 15 of the Commission’s Rules Regarding Ultra-Wideband Transmission Systems),” *FCC 02-48*, adopted Feb. 14, 2002, released Apr. 22, 2002.
- [2] W.A. Kissick, Ed., “The temporal and spectral characteristics of ultrawideband signals,” NTIA Report 01-383, Jan. 2001.
- [3] J.R. Hoffman, M.G. Cotton, R.J. Achatz, R.N. Statz, and R.A. Dalke, “Measurements to determine potential interference to GPS receivers from ultrawideband transmission systems,” NTIA Report 01-384, Feb. 2001.
- [4] J.R. Hoffman, M.G. Cotton, R.J. Achatz, and R.N. Statz, “Addendum to NTIA Report 01-384: Measurements to determine potential interference to GPS receivers from ultrawideband transmission systems,” NTIA Report 01-389, Sep. 2001.
- [5] J.R. Hoffman, E.J. Haakinson, and Y. Lo, “Measurements to determine potential interference to public safety radio receivers from ultrawideband transmission systems,” NTIA Report 03-396, Apr. 2003.
- [6] M. Cotton, R. Achatz, J. Wepman, B. Bedford, “Ultrawideband interference potential: Part 1 – Procedures to characterize ultrawideband emissions and characterize interference susceptibility of C-band satellite digital television receivers,” NTIA Report TR-05-419, Feb. 2005.
- [7] J.C. Whitaker, “Digital television transmission systems,” Ch. 13 in *Standard Handbook of Video and Television Engineering*, J.C. Whitaker, Ed., New York, NY: McGraw-Hill, 2000.
- [8] L.R. Espeland and A.D. Spaulding, “Amplitude and time statistics for atmospheric radio noise,” ESSA Technical Memorandum, ERLTM-ITS 253, Sep. 1970.
- [9] F. Sanders, “Measurements of pulsed co-channel interference in a 4-GHz digital earth station receiver,” NTIA Report 02-393, May 2002.
- [10] ETS 300 421: “Digital broadcasting systems for television, sound, and data services: Framing structure, channel coding, and modulation for 11/12 GHz satellite services,” *European Telecommunications Standards Institute*, Dec. 1994.
- [11] ETSI TR 101 290: “Digital Video Broadcasting (DVB); Measurement guidelines for DVB systems,” *European Telecommunications Standards Institute*, v1.2.1, 2001.